



FasTrac CS309 WB

WATER BASED CONCRETE CURE & SEAL

Product Description

FasTrac CS309 WB is a water based, modified acrylic compound used to cure, seal and dustproof freshly placed and finished concrete substrates. It complies with ASTM C309, Type I, Class B, ASTM C309 Type I, Class A/B and AASHTO M148, Type I, Class A/B.

Applications

- New and old concrete
- Interior and exterior

Features

- Low odor, VOC compliant, environmentally friendly formula
- Meets ASCTM C309
- Water based, non-flammable

Application

STIR THOROUGHLY IN ORIGINAL CONTAINER BEFORE APPL YING. DO NOT THIN OR DILUTE.

New Concrete

Apply CS309 with a low pressure spray, roller or brush after the bleed water has disappeared and surface cannot be marred.

Old Concrete

Surface must be clean, dry, and sound, free of dust, oil, grease, and sealers. Pressure water washing is the preferred method of preparation.

Do not over apply or soak concrete with CS309.

Limitations

Minimum surface temperature is 4°C.

Do not dilute.

Do not allow to freeze.

Clean up

Collect with absorbent material. Flush area with water. Dispose of in accordance with local, state and federal disposal regulations.

Coverage

1st coat: 200-400 sq. ft./ 4.9-9.8 m² /L

2nd coat: 400-600 sq. ft./ 9.8-14.8 m² /L

Packaging

- 3.8 Litre
- 18.9 Litre
- 208 Litre

Shelf Life and Storage

18 months in original un-opened container between 5°C - 35°C.



FasTrac CE309 WB

WATER BASED CONCRETE CURE & SEAL

TECHNICAL DATA

Condition material to:	18°C - 29°C before using.
Flash point	93°C
Freezing point	0°C
Flammability	None
VOC	< 100 g/L
Dry time / recoat time @ 23°C	~ 1 hour
Light foot traffic	2 - 3 hours
Normal traffic	12 hours
Water retention, kg/m ²	0.44
Percent Solids	>15%

Warranties and Disclaimers

Hychem warrants that this product shall conform to the technical specifications published in the product literature. The quality and fitness of the product is dependent upon the proper use and application of the product by the applicator. Hychem has no role in the application of the finished polymer other than to manufacture and supply its components. It is vital that the person applying this product understands the product and is fully trained and certified in the use of spray equipment and application of sol-gel materials. There are no warranties that extend beyond the description on the face of this instrument, except when provided in writing, directly by Hychem and executed under seal by a company officer.

Field Support

Field support where provided, does not constitute supervisory responsibility. Suggestions made by HYCHEM either verbally or in writing may be followed, modified or rejected by the owner, engineer or contractor since they and not HYCHEM are responsible for carrying out procedures appropriate to a specific application.

Customer Responsibility

The technical information and application advice given in this publication is based on the best information available at the time of print. As the information herein is of a general nature, no assumption can be made as to the product suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by Commonwealth or State Legislation. The owner, his representative or the contractor is responsible for checking the suitability of products for their intended use.